

PRODUCT INFORMATION



DESIGN

The biggest insert in ALBERO line with wide panoramic vision of fire available only with guillotine reinforced door.

QUALITY

Fireplace inserts are made of high-quality P265GH boiler steel, which is resistant to continuous operation at higher temperature. A well reinforced door profile is used.

REPEATABILITY

Production process use modern machinery park: welding robots, press brakes, laser cutters.

ECOLOGY

Comply with strict emission standards and the ECODSIGN, thanks to the use of an after-burning system and high efficiency.

SECURITY

An innovative ventilated handle protects against scalding. Suitable for homes with recuperation.

EASY-TO-USE

The built-in double intake with the throttles enables smooth integrated regulation of the amount of air supplied.

CLEANLINESS

The air curtain provides the effect of „clean glass“. Combustion chamber without grate can be easily cleaned with ash vacuum cleaner.

| | |
|--|---------------|
| Nominal power [kW] | 25 |
| Heating load range [kW] | 12,5-32,5 |
| Thermal efficiency [%] | 80 |
| CO emission (by13% O ₂) [g/m ³] | 1,215 |
| Dust emission [g/m ³] | 0,028 |
| Average fuel consumption [kg/h] | 8 |
| Recommended active area of outlet grids [cm ²] | 1750-2000 |
| Recommended active area of inlet grids [cm ²] | 1000-1630 |
| Dimensions of the glass [mm] | 1200x430 |
| External dimensions [mm] | 1503x1760x690 |
| Max. log length [mm] | 800 |
| Diameter of the flue [mm] | 250 |
| Inlet diameter [mm] | 150 |
| Weight [kg] | 431 |
| Efficiency coefficient | 107 |
| Energy class | A+ |

OTHER EQUIPMENT:

Ceramic deflector, heat pipes, steel flue, adjustable feet (+4 cm), heat radiators.

ADDITIONAL OPTIONS:

Masking frames 3/4 and 4/4, additional legs (+10 cm), printed DECOR glass.

